



194.00 EUR
incl. 19% VAT, plus [shipping](#)

Support: [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports Daul Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Mini-ITX Form Factor(148mm x 102mm)

- | | |
|---------------------|---|
| 1. CPU | 1. INTEL ® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB) |
| 1. Chipset | 1. INTEL® 945GSE + ICH7M chipset |
| 1. Memory | 2. Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB) |
| 1. Storage | 3. Front Side Bus 533MHz |
| 1. Audio | 1. 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB |
| 1. Ethernet LAN | 1. 1 * Serial ATA2 3Gb/s connectors |
| 1. LVDS | 2. 1 * Ultra DMA 133/100 IDE connector |
| 1. USB | 1. Realtek ALC662 6-Channel HD Audio Codec |
| 1. Special Features | 1. 2 * Realtek RTL8111DL PCI-E Gigabit Ethernet LAN |
| 1. Rear Panel I / O | 1. Onboard 18-bit dual channel LVDS connector |
| | 1. Embedded 4 * USB 2.0 |
| | 2. |
| | 1. Intel Diamond Ville Platform |
| | 2. Support ACPI S3 |
| | 3. Support CPU Smart FAN |
| | 1. 2 * USB 2.0 ports |
| | 2. 1 * PS KB connector |
| | 3. 2 * RJ-45 port |
| | 4. 3 * Audio I/O ports (Line-in, MIC and line-out) |
| | 5. 1 * 12V DC jack |
| | 6. 1 * DVI-I port |

1. Internal I / O

1. 1* USB 2.0 headers for 2 USB 2.0 ports
2. NB / Chassis Fan connectors;
3. 1 * 20-pin ATX Power connector
4. 1 * 32-pin LVDS header & 1 * GPIO header & 1 * Parallel header
5. 2 * RS232 COM headers & 1 * RS422/485 header
6. 1 * Audio header & 1 * CF CARD header
7. 1 * Mini PCI-E connector

1. BIOS

1. Award 8MB DIP Flash ROM

1. Form Factor

1. Mini ITX Form Factor(148mm x 102mm)

1. Functional

1. ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation

1. Certificate

1. CE, FCC, RoHS

1. Temperature

1. Operating within 0~60 centigrade
2. Storage within -20-85 centigrade

Product Accessories

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable