

1194.00 EUR
incl. 19% VAT, plus [shipping](#)



- 17.0" 350 nits high brightness SVGA TFT LCD with LED backlight
- Onboard Intel® Q170 Express Chipset
- Supports Intel LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- 2* Dual Channel DDR4 2133MHz up to 32GB
- Support Dual Intel® Gigabit LAN
- Support 4 * COM ports (COM1/3 Support RS232/422/485)
- Support 6*USB3.0 Ports
- Support 2.5" SATA HDD, 1 * M-SATA connector
- Support 1*PCI or PCI-Ex16 , 2 * Mini PCI-E
- Support Camera for remote monitoring
- Plastic and IP65-rated front bezel

Display	
Front Bezel	- IP65, NEMA 4 rugged protection, metal front bezel
Display Type	- 17.0" With LED Backlight
Brightness (cd/m²)	- 350 nits
Display Color	- 262K

Resolution	- 1280 x 1024 @ 60Hz
Viewing Angle (H/V)	- 170°/160°
Pixel Pitch	- 0.264 x 0.264 mm
Aspect Ratio	- 4:3
Contrast Ratio	- 1000:1
Response Time	- 3.5 ms
Touch screen	
Type	- 5 wires analog resistive type
Active Range	- 337.00 x 269.50mm ±0.2mm
Transparency	- 80 ±3%
Operating Force	- ■ 80g
Knock test	- 10,000,000 times keystrokes
Main System	
CPU	- Intel® LGA1151 Socket
RAM	- DDR4 2133MHz Max 32GB
BIOS	- 128MB SPI Flash ROM
Storage	- 1 * 2.5" SATA HDD - 1 * M-SATA connector
Watchdog Timer	- 255 levels, 0~255 sec.
OS Support	- Windows 7 / 8.1 / 10 / Linux
I/O Connector	
I/O Ports and Switches	- 6 * USB3.0 - 2 * RS232 - 2 * RS232/422/485 - 1 * DVD-D,HDMI,DP - 2 * LAN (Intel® I211AT+I219LM Gigabit LAN) - 1 * 110~240V AC input - 1 * Audio Jack - 1 * Expansion card - 1 * Power button
Expansion Interface	
Expansion	- 2 * PCI-E mini card for WIFI or 4G/3G
Power	
Power Input	- AC version: 100~240V AC
Dimensions	
Case Dimensions	- 421*354*91mm
Packing Dimensions	- 421*354*91mm
Certifications	
Certifications	- CE, FCC■IP65 (Front)
Environment	
Temperature	- Operating: -10°C ~ 60°C (with W.T. DRAM/HDD in airflow condition) - Operating: -10°C ~ 60°C (with W.T. DRAM/HDD) - Storage: -20°C ~ 65°C
Shock	- Operating: 15G■11ms duration
Vibration	- Operating: 5~500Hz/1 Grms
Warranty	
Warranty	- The warranty of 2 years, panel the warranty of 1 year