



1598.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- i5-1135G7 !
- 21,5" Panel Computer !



- 1. 21.5" 250 nits TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Support Open frameless design
- Aluminum Die-Cast Panel PC series, Easy HDD and DARM installation, cableless design
- 12-36V DC-in, with Electrical Over Stress (EOS) and OVP design
- Front bezel meets IP65-rated protection
- VESA Support 100x100mm

Display	– IP65, NEMA 4 rugged protection, metal front bezel – 21.5" With LED Backlight – 250 nits – 16.7M display color – 1920 x 1080 @60Hz resolution – 170°/160° viewing angle (H/V) – 0.24825 x 0.24825mm pixel pitch – 16:9 aspect ratio – 1000:1 contrast ratio – 8ms response time
---------	---

Touch Screen	– Projected capacitive type – 386.81 x 237.12mm ±0.3mm active range – Transparency ■ 85% – Surface Hardness ■ 6H (JIS-5400)
Case	– Aluminum panel – Iron case – White color – Spray paint coating requirement
Main System	– Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor – 2* DDR4 SO-DIMM (Max 64GB) – 256MB SPI Flash ROM – Watchdog Timer 256 levels, 0~255 sec. – OS Support Windows 10 / Linux
Expansion	– 1* M.2 E key (2230) for WIFI – 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)
Storage	– 1* 2.5" SATA HDD – 1* M.2 M key (2242/2280, PCI-Ex4)
I/O Connector	– 2* USB3.2 (Gen. 2) – 4* USB2.0 – 2* RS232/422/485 – 2* RS232 (option 16bit GPIO) – 1* HDMI – 1* AT/ATX Mode Button – 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE) – 1* 12~36V DC-in Locking Jack – 1* Power button – 1* 2pin Front Power button
Power Input	– 12~36V DC-in – AC version: 100~240V AC-DC 90W power adapter or – DC version: 12VDC with over current protection fuse
Power Consumption	– 45W
Dimensions	– 535.80 * 327.31 * 68.50 mm
Compliance	– CE, FCC, IP65 (Front, option)
Safety	– Shock: 1ms duration – Vibration: 5~500Hz/1 Grms
Temperature	– Operating: : -10°C ~ 60°C – Storage: -20°C ~ 70°C